

Nominal Diameter

5 = 20 mm²

Rectus Series

17



Brass/steel industrial coupling with English profile specifically suited to compressed air applications in industry. Coupling system with single-hand operation, High Flow valve for optimum flow and low pressure drop. Versatile due to slim design and light weight.

Series 17 with additional end connections available on request.

Working Temperature*

-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure****

35 bar

** maximum static working pressure with design factor 4 to 1.

Material

Coupling: Brass nickel plated,
Steel zinc plated

Plug: Steel nickel plated

Seals: NBR

Technical Description

Connecting Force 0 bar: 35 N


Connecting Force 6 bar: 115 N

Vacuum Coupling: 96%

Vacuum connected: 96%

Interchangeability (KA only)




- Schrader DN 5

Flow diagrams**Air**



Couplings – with valve




Series 17KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 <p>Male Thread</p>	R 1/4	19	63	12	23	17KAAK13SPN
	R 3/8	19	62	12	23	17KAAK17SPN
	R 1/2	22	63	17	23	17KAAK21SPN
 <p>Female Thread</p>	G 1/4	19	58	9	23	17KAIW13SPN
	G 3/8	19	57	9	23	17KAIW17SPN
	G 1/2	24	60	12	23	17KAIW21SPN
 <p>Hose Barb</p>	6 mm	19	76	25	23	17KATF06SPN
	8 mm	19	76	25	23	17KATF08SPN
	10 mm	19	76	25	23	17KATF10SPN
	13 mm	19	76	25	23	17KATF13SPN



Plugs – without valve

Series 17KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 <p>Male Thread</p>	R 1/8	11	37	9		17SFAK10SXN
	R 1/4	14	42	12		17SFAK13SXN
 <p>Female Thread</p>	G 1/8	14	33	7		17SFIW10SXN
	G 1/4	17	36	9		17SFIW13SXN
 <p>Hose Barb</p>	6 mm		58	25	12	17SFTF06SXN
	8 mm		52	25	12	17SFTF08SXN
	10 mm		52	25	12	17SFTF10SXN